

Main Features

- Low VSWR, high isolation
- Low PIM, low insertion loss
- Compact design for easy installation
- Customized band is available
- AISG/DC bypass



Electrical Specifications

Items	Value
Frequency	CH1: 698-803MHz
	CH2: 880-960MHz
	CH3: 1710-1880MHz
	CH4: 1920-2200MHz
Return loss	≤-19dB
Insertion loss	≤0.3dB
Isolation	≥50dB
Power handling	300W
Intermodulation (3rd order)	≤-155dBc @ 2 x 20W
Impedance	50Ω
DC Characteristic	DC bypass all ports


Environmental Specifications

Items	Value
Operating temperature range	-25°C to +65°C
Storage temperature range	-40°C to +85°C
Relative humidity	5%-95%
Applications	IP67

Mechanical Specifications

Items	Value
Dimension	279 x 282 x 69 (mm, Including brackets and connectors)
Weight	≤4.0kg
Connectors type	4.3-10 female
Mounting	Wall or pole
Packing	1Pcs in box

Outline Drawing



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.