

PFC50E-12CB

1/2"R Coaxial Cable

PROSE

- 1/2" Foam Insulation Coaxial Cable
- Corrugated copper outer conductor
- Black PE jacket
- Recommended operating frequency: 1~6000 MHz
- This product is used for telecommunication system
- Outdoor application, UV resistance, halogen free



Photo for reference

Material

Inner conductor material	Copper-Clad Aluminium Wire
Dielectric material	Foam PE
Outer conductor material	Corrugated copper(Annularly)
Jacket material	PE, Black, Halogen free

Dimensions

Nominal size	1/2"
Inner conductor OD.	Ø 4.8 mm
Dielectric OD.	Ø 12.2 mm
Outer conductor OD.	Ø 13.8 mm
Jacket OD.	Ø 15.9 mm

Reference standard

UV Resistance	UL 1581 or IEC 60068-2-5
---------------	--------------------------

Electrical Specification

Impedance	50 ± 1 Ω
Relative Velocity of Propagation	86 %
Capacitance	76 pF/m
Inductance	0.190 μH/m
Maximum Operating Frequency	8.8 GHz
Cut-off Frequency	8.8 GHz
Peak Power Rating	40 kW
Insulation Resistance	≥ 10 GΩx km

DC Breakdown Voltage	6000 V
Jacket Spark Test Voltage	8000 Vrms

Environmental Specification

Installation Temperature	-40°C to +60°C
Operating Temperature	-50°C to +85°C
Storage Temperature	-50°C to +85°C
RoHS	Compliant

Standard Conditions

Attenuation, Ambient Temperature	20°C
Average Power, Ambient Temperature	40°C
Average Power, Inner Conductor Temp	100°C

Mechanical Specification

Tensile strength	1100 N
Min. bending radius (single)	70 mm
Min. bending radius (repeated)	125 mm
Number of bends, minimum (typical)	15 (50)
Bending moment	5 Nm
Recommended hanger spacing	0.8 m

Return Loss

Return loss(Band A)	≥26dB 617 to 960MHz
Return loss(Band B)	≥26dB 1700 to 2200MHz
Return loss(Band C)	≥24dB 2200 to 2700MHz
Return loss(Band D)	≥23dB 3400 to 4200MHz
Return loss(Band E)	≥22dB 5150 to 5925MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Average Power(kW)
100	2.15	3.94
200	3.08	2.75
300	3.81	1.99
400	4.46	1.80

450	4.70	1.75
800	6.35	1.33
900	6.75	1.25
1000	7.20	1.18
1800	9.90	0.86
2000	10.50	0.81
2200	11.10	0.77
2500	11.95	0.73
2700	12.47	0.69
3000	13.20	0.65
3500	14.40	0.59
3600	14.64	0.58
3800	15.12	0.56
4000	15.50	0.55
5000	17.60	0.48
6000	19.60	0.43

*Maximum attenuation value shall be 105% of the nominal attenuation value.

Marking on cable

PROSE _ PFC50E-12CB _ 50Ω _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within ±0.5% accuracy.
Remark2: (DD+MM+SS+YY+NNNNN) means cable code.
Remark3: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.