

PLAC50E-114A

1-1/4"R Coaxial Cable

PROSE

- 1-1/4" Foam Insulation Coaxial Cable
- Corrugated aluminium outer conductor
- Black PE jacket
- Recommended operating frequency: 1~3800 MHz
- This product is used for telecommunication system
- Outdoor application, UV resistance, halogen free



Photo for reference

Material

Inner conductor material	Copper tube, helical
Dielectric material	Foam PE
Outer conductor material	Corrugated aluminium (Annularly)
Jacket material	PE, Black, Halogen free

Dimensions

Nominal size	1-1/4"
Inner conductor OD.	Ø 13.8 mm
Dielectric OD.	Ø 33.5 mm
Outer conductor OD.	Ø 36.0 mm
Jacket OD.	Ø 38.6 mm

Reference standard

UV Resistance	UL 1581 or IEC 60068-2-5
---------------	--------------------------

Electrical Specification

Impedance	50 ± 1 Ω
Relative Velocity of Propagation	88 %
Capacitance	75 pF/m
Cut-off Frequency	3.8 GHz
Peak Power Rating	185 kW
Insulation Resistance	≥ 5 GΩx km
DC Breakdown Voltage	10000 V
Jacket Spark Test Voltage	10000 Vrms

Environmental Specification

Installation Temperature	-25°C to +60°C
Operating Temperature	-40°C to +85°C
Storage Temperature	-70°C to +85°C
RoHS	Compliant

Standard Conditions

Attenuation, Ambient Temperature	20°C
Average Power, Ambient Temperature	40°C
Average Power, Inner Conductor Temp	100°C

Mechanical Specification

Tensile strength	1600 N
Min. bending radius (single)	150 mm
Min. bending radius (repeated)	380 mm
Number of bends, minimum (typical)	15 (50)
Bending moment	40 Nm
Recommended hanger spacing	1.2 m

Return Loss

Return loss(Band A)	≤ -23dB 800 to 1000MHz
Return loss(Band B)	≤ -23dB 1700 to 2500MHz
Return loss(Band C)	≤ -23dB 2500 to 2700MHz
Return loss(Band D)	≤ -20.8dB 3300 to 3800MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Average Power(kW)
100	0.90	7.60
200	1.31	5.24
300	1.70	4.03
400	1.95	3.51
450	2.04	3.35
800	2.83	2.45
900	3.02	2.26

1000	3.21	2.12
1500	4.07	1.70
1800	4.53	1.52
2000	4.83	1.40
2200	5.10	1.33
2400	5.37	1.26
2500	5.45	1.24
2600	5.51	1.23
2700	5.62	1.20
3000	6.19	1.09
3500	6.80	0.99
3600	6.87	0.98
3800	7.21	0.94

*Maximum attenuation value shall be 105% of the nominal attenuation value.

Marking on cable

PROSE _ PLAC50E-114A _ 50Ω _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within $\pm 0.5\%$ accuracy.
Remark2: (DD+MM+SS+YY+NNNNN) means cable code.
Remark3: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.