

PR-CLX-P3

Cable lug pin type

PROSE

- High grade tinned copper
- Widely field application
- Different size available
- Simple operation and easy wiring



Photo for reference

Part number

PR-CLX-P3	Cable lug pipe type, X indicate the suitable cable conductor
-----------	--

Available PNs

Conduct	d(mm) ±0.3	D(mm) ±0.3	W(mm) ±0.5	B(mm) ±0.5	L(mm) ±0.8	H(mm) ±0.8	T(mm) ±0.07	
10mm ²	4.5	6.9	4.3	8.0	22.0	2.4	1.1	
16mm ²	5.9	8.4	5.5	10.0	26.0	2.6	1.2	
25mm ²	7.0	9.5	6.8	13.5	33.5	2.6	1.2	
35mm ²	8.7	11.8	8.0	16.0	40.5	3.2	1.5	
50mm ²	9.8	13.6	9.5	19.0	45.0	3.8	1.8	
70mm ²	11.6	15.8	11.0	24.0	55.0	4.2	2.0	
95mm ²	13.7	18.9	12.5	24.0	55.0	5.2	2.0	
120mm ²	15.1	21.3	14.3	26.0	62.0	6.2	3.0	

Material

Material	Copper, T2
Surface finish	Tinned

Environment

RoHS	Compliant
------	-----------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.