

# PR-RC3TB-DF-C05


DIN female connector for 7/8" flexible cable

**PROSE**

## Part number

|                 |                                              |
|-----------------|----------------------------------------------|
| PR-RC3TB-DF-C05 | DIN female connector for 7/8" flexible cable |
|                 | According to IEC61169-4                      |

## Part list

| NO. | Description     | Material        | Plating   | Photo for reference                                                                |
|-----|-----------------|-----------------|-----------|------------------------------------------------------------------------------------|
| 1   | Inner conductor | Bronze          | Ag        |  |
| 2   | Insulator       | PTFE            |           |                                                                                    |
| 3   | Body            | Brass           | Tri-alloy |                                                                                    |
| 4   | Nut             | Brass           | Nickel    |                                                                                    |
| 5   | Washer          | Brass           | Nickel    |                                                                                    |
| 6   | Gasket          | Silicone rubber |           |                                                                                    |

## Document

|          |                                       |
|----------|---------------------------------------|
| Document | MA_RC3TB-7/8 installation instruction |
|----------|---------------------------------------|

## Electrical data

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Characteristics impedance       | 50Ω                                  |
| Frequency                       | DC to 5GHz                           |
| Insulation resistance           | ≥5000MΩ                              |
| Center contact resistance       | 0.4mΩ                                |
| Outer contact resistance        | 0.2mΩ                                |
| Dielectric withstanding voltage | 4000V rms                            |
| Operating voltage               | 1000V rms                            |
| Insertion loss                  | $0.05 \cdot \sqrt{F} \text{ GHz dB}$ |
| Return loss                     | ≤-30dB @ DC-1.0GHz                   |
|                                 | ≤-28dB @ 1.0-2.2GHz                  |
|                                 | ≤-26dB @ 2.2-2.7GHz                  |
|                                 | ≤-24dB @ 2.7-3.8GHz                  |
|                                 | ≤-22dB @ 3.8-5.0GHz                  |
| DTF                             | ≤-35dB @DC-1.0GHz                    |
|                                 | ≤-32dB @1.0-2.7GHz                   |
|                                 | ≤-28dB @2.7-3.8GHz                   |
|                                 | ≤-26dB @3.8-5.0GHz                   |

|                                         |                   |
|-----------------------------------------|-------------------|
| Intermodulation (3 <sup>rd</sup> Order) | ≤-160dBc, 2x43dBm |
|-----------------------------------------|-------------------|

## Mechanical data

|                                   |                     |
|-----------------------------------|---------------------|
| Interface                         | DIN female          |
| Suitable cable                    | 7/8" flexible cable |
| Mating cycles                     | ≥500 times          |
| Coupling nut retention            | ≥450N               |
| Connector torque proof recommend  | 25 to 30 N.m        |
| Center contact captivation, axial | ≥200N               |
| radial                            | ≥2 Ncm              |

## Environment

|                              |                                           |
|------------------------------|-------------------------------------------|
| Working temperature          | -45°C to +85°C                            |
| Installation Temperature     | -40°C to +50°C                            |
| Anti-UV                      | IEC 60068-2-5                             |
| Salt spray test Standard     | 48hr (IEC 60068-2-11)                     |
| Mechanical Shock Test Method | MIL-STD-202, Method 213, Test Condition D |
| Vibration Test Method        | MIL-STD-202, Meth. 204, Cond. A           |
| IP protection                | IP68, 24h @1m, 20°C                       |
| RoHS                         | Compliant                                 |

### Notice

- 1, The connection should be covered with addition weatherproof kits for long time duration.
- 2, Connection molding shape may be changed during the product life-time due to the manufacture skill upgrade.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.