

- 7/8" Foam Insulation Leaky Cable
- Slotted copper foil outer conductor
- Black flame retardant polyolefin jacket
- Recommended operating frequency: 698~3800 MHz
- The leaky cable is used in tunnels and subway, etc.
- Indoor application, flame retardant, low smoke, halogen free



Photo for reference

Material

Inner conductor material	Copper Tube
Dielectric material	Foam PE
Outer conductor material	Copper foil
Jacket material	Flame retardant polyolefin, Black, Halogen free

Dimensions

Nominal size	7/8"
Inner conductor OD.	Ø 9.45 mm
Dielectric OD.	Ø 22.8 mm
Outer conductor OD.	Ø 23.5 mm
Jacket OD.	Ø 27.2 mm

Reference standard

Flame retardant property	IEC 60332-1-2, IEC 60754-1/-2, IEC 61034-2
--------------------------	--

Electrical Specification

Impedance	50 ± 2 Ω
Capacitance	75 pF/m
Insulation Resistance	≥5000 MΩx km
Insulation Voltage	10000 V
Jacket Spark Test Voltage	8000 V
Relative Velocity of Propagation	89 %
Peak power	91kW
Operating Frequency Band	5~3800 MHz

Optimum Operating Frequency Band	698~3800 MHz
Stop Band	1090-1100MHz & 2170-2200MHz & 2725-2750MHz & 3270-3300MHz
VSWR	≤1.3 75 MHz to 150MHz
	≤1.3 698MHz to 960MHz
	≤1.3 1700MHz to 2025MHz
	≤1.3 2110MHz to 2170MHz
	≤1.3 2300MHz to 2700MHz
	≤1.3 3300MHz to 3630MHz
	≤1.3 3700MHz to 3800MHz

Environmental Specification

Installation Temperature	-40°C to +80°C
Operating Temperature	-55°C to +85°C
Storage Temperature	-55°C to +85°C
RoHS	Compliant

Polarization mode

Polarization	5-500MHz	Radial
	698-3800MHz	Vertical

Mechanical Specification

Minimum Bend Radius:	
Single Bend	250 mm
Multiple Bend	500 mm
Bending Moment	14.9 N·m
Minimum Distance to Wall	50 mm
Recommended Hanger Spacing	0.8 m to 1.2m
Tensile Strength	1350 N

Standard Conditions

Attenuation Test Method	IEC 61196-4
Attenuation Tolerance	±5 %
Attenuation Ambient Temperature	20 °C
Average power, ambient temperature	40 °C
Average power, inner conductor temperature	100 °C

Coupling Loss Test Method	IEC 61196-4
Coupling Loss Tolerance	±5 dB

Attenuation and Coupling Loss

Frequency (MHz)	Attenuation (dB/100m)	Coupling Loss (2m) 50% (dB)	Coupling Loss (2m) 95% (dB)
698	3.50	80	83
800	4.00	72	78
900	4.30	71	76
960	4.50	70	76
1800	6.70	68	73
1900	6.90	68	72
2000	7.30	68	73
2100	7.60	68	72
2200	8.00	68	72
2300	8.30	68	72
2400	8.80	68	72
2600	9.40	68	70
2700	10.00	68	70
3400	12.00	66	69
3500	12.50	66	68
3600	13.00	65	68
3700	14.00	64	66
3800	15.00	63	66

Marking on cable

PROSE _ PRC50FR-78B _ 50Ω _ _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within ±0.5% accuracy.
Remark2: (DD+MM+SS+YY+NNNNN) means cable code.
Remark3: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.