

- Long lasting body with high strength
- Protection rating IP68
- Cable ports with mechanical sealing



## Part number

|                                                                                                                                            |                          |
|--------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| PRJC-D-5601-XX-X                                                                                                                           | Joint closure, dome type |
| 1 2 3 4                                                                                                                                    |                          |
| *1 indicate the dome closure                                                                                                               |                          |
| *2 indicate the closure type                                                                                                               |                          |
| *3 indicate the cores: 24: 24F 48:48F...                                                                                                   |                          |
| *4 indicate the application: W: wall mount; P: pole mount; UG: underground; AR: Aerial mount; D: Duct; ALL: All applications are supported |                          |

## Specifications

| Item                         |                | Parameters                                       |
|------------------------------|----------------|--------------------------------------------------|
| Dimensions(mm)               |                | 455 × Φ225                                       |
| Material                     | Closure        | PP+GF                                            |
|                              | Metallic Parts | Stainless steel 304                              |
| Sealing Method               |                | Mechanical sealing                               |
| Protection Rating            |                | IP68                                             |
| Cable ports                  | Oval port      | 1                                                |
|                              | Branch port    | 4                                                |
| Cable Diameter (mm)          |                | φ8~18                                            |
| No. of Fibers/tray           |                | 24                                               |
| Max. No of Splice Tray (pcs) |                | 6                                                |
| Max. Capacity of Fibers      |                | 144                                              |
| Installation Method          |                | Wall mounting, aerial mounting, or direct burial |

## Environmental data

|                   |           |
|-------------------|-----------|
| 2011/65/EC (RoHS) | Compliant |
|-------------------|-----------|

## Package

|          |            |
|----------|------------|
| Standard | 1 set /box |
|----------|------------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.