

- Long lasting body with high strength
- Protection rating IP68
- Cable ports with mechanical sealing



Part number

PRJC-IL-6806-XX-X	Joint closure, In-line type
1 2 3 4	
*1 indicate the in-line closure	
*2 indicate the closure type	
*3 indicate the cores: 24: 24F 48:48F...	
*4 indicate the application: W: wall mount; P: pole mount; UG: underground; AR: Aerial mount; D: Duct; ALL=All applications	

Specifications

Item		Parameters
Dimensions(mm)		474(L)×201(W)×107(H)
Material	Closure	PP+GF
	Metallic Parts	Stainless steel 304
Sealing Method		Mechanical sealing
Protection Rating		IP68
No. of In-out Ports		4
Cable Diameter (mm)		φ10~20
No. of Fibers/tray		24
Max. No of Splice Tray (pcs)		3
Max. Capacity of Fibers		72
Installation Method		Wall mounting, aerial mounting, or direct burial

Environmental data

2011/65/EC (RoHS)	Compliant
-------------------	-----------

Package

Standard	1 set /box
----------	------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.