

- High grade aluminum alloy wire
- AL Alloy/PVC/PVC
- Solid or stranded conductor
- Rated voltage: 0.6/1kV
- Rated temperature: 70°C
- This product used for power transmission




Photo for reference

Part number

PAAWYYR6-XCXXmm2-X	Power cable
1 2 3	
*1 indicate the core quantity, 1-1core, 2-2cores, 3-3cores, 4-4cores, 5-5cores.	
*2 indicate the single core section area.	
*3 indicate the insulation colour, the meaning of the numbers is in the "colour code" table.	

For example:

Part No.	Description
PAAWYYR6-2C10mm2-1	2x10mm ² , Al alloy conductor, Blue and Brown PVC insulation, Black PVC sheath

Colour code

Insulation colour: The meaning of the number or letter is as below.

1 core:

C.C.	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Violet	Yellow/Green
Abb.(XX)	BL	OR	GN	BN	GY	WH	RD	BK	YW	VT	YG

2 cores:

Number	0	1	2	3	4	5	6
Colour	Red, Blue	Blue, Brown	Blue, Black	Blue, Grey	Black, Grey	Red, Black	Black, White

3 cores:

Number	0	1	2	3
Colour	Yellow, Green, Red	Blue, Black, Brown	Blue, Brown, Yellow/Green	Red, Yellow, Blue
Number	4	5	6	7
Colour	Brown, Black, Grey	Red, Blue, Yellow/Green	Black, White, Red	Black, Blue, Green

4 cores:

Number	0	1	2
Colour	Blue, Yellow, Green, Red	Blue, Brown, Black, Grey	Red, Blue, Yellow, Black

Number	3	4	5
Colour	Grey, White, Red, Blue	Blue, Brown, Black, Yellow/Green	Black, Brown, Grey, Yellow/Green
5 cores:			
Number	0	1	2
Colour	Blue, Yellow, Green, Red, Black	Yellow/Green, Blue, Brown, Black, Grey	Red, Yellow, Blue, Brown, Green
Sheath colour: Black			

Standard

Ref. standard	IEC 60502-1
---------------	-------------

Material and dimension

No.	Item		PAAWYYR6-XCXXmm2-X	
1	Conductor	Material	Aluminum alloy wire	Class 1 for section $\leq 6\text{mm}^2$ Class 2 for others
2	Insulation	Material	PVC/A	
3	Filler	Material	Optional	
4	Tape	Material	Optional	
5	Sheath	Material	PVC, ST1	

PN	Max. Conductor resistance, 20°C (Ω/km)	Nom. Insulation thickness (mm)	Min. Sheath thickness (mm)	Approx. Overall Diameter, (mm)
PAAWYYR6-1C6mm2-X	4.61	1.0	0.92	7.2
PAAWYYR6-1C10mm2-X	3.08	1.0	0.92	8.5
PAAWYYR6-1C16mm2-X	1.91	1.0	0.92	9.5
PAAWYYR6-1C25mm2-X	1.20	1.2	0.92	11.0
PAAWYYR6-1C35mm2-X	0.868	1.2	0.92	12.1
PAAWYYR6-1C50mm2-X	0.641	1.4	0.92	13.5
PAAWYYR6-1C70mm2-X	0.443	1.4	0.92	15.3
PAAWYYR6-1C95mm2-X	0.320	1.6	1.00	17.5
PAAWYYR6-2C6mm2-X	4.61	1.0	1.24	13.3
PAAWYYR6-2C10mm2-X	3.08	1.0	1.24	15.9
PAAWYYR6-2C16mm2-X	1.91	1.0	1.24	17.9
PAAWYYR6-2C25mm2-X	1.20	1.2	1.24	20.9
PAAWYYR6-2C35mm2-X	0.868	1.2	1.24	23.1
PAAWYYR6-2C50mm2-X	0.641	1.4	1.24	25.9
PAAWYYR6-2C70mm2-X	0.443	1.4	1.32	29.7

PN	Max. Conductor resistance, 20°C (Ω/km)	Nom. Insulation thickness (mm)	Min. Sheath thickness (mm)	Approx. Overall Diameter, (mm)
PAAWYYR6-2C95mm2-X	0.320	1.6	1.40	33.8
PAAWYYR6-3C6mm2-X	4.61	1.0	1.24	14.0
PAAWYYR6-3C10mm2-X	3.08	1.0	1.24	16.8
PAAWYYR6-3C16mm2-X	1.91	1.0	1.24	19.0
PAAWYYR6-3C25mm2-X	1.20	1.2	1.24	22.2
PAAWYYR6-3C35mm2-X	0.868	1.2	1.24	24.6
PAAWYYR6-3C50mm2-X	0.641	1.4	1.24	27.6
PAAWYYR6-3C70mm2-X	0.443	1.4	1.40	31.8
PAAWYYR6-3C95mm2-X	0.320	1.6	1.48	36.3
PAAWYYR6-4C6mm2-X	4.61	1.0	1.24	15.3
PAAWYYR6-4C10mm2-X	3.08	1.0	1.24	18.4
PAAWYYR6-4C16mm2-X	1.91	1.0	1.24	20.8
PAAWYYR6-4C25mm2-X	1.20	1.2	1.24	24.5
PAAWYYR6-4C35mm2-X	0.868	1.2	1.24	27.1
PAAWYYR6-4C50mm2-X	0.641	1.4	1.32	30.7
PAAWYYR6-4C70mm2-X	0.443	1.4	1.48	35.4
PAAWYYR6-4C95mm2-X	0.320	1.6	1.56	40.4
PAAWYYR6-5C6mm2-X	4.61	1.0	1.24	16.7
PAAWYYR6-5C10mm2-X	3.08	1.0	1.24	20.2
PAAWYYR6-5C16mm2-X	1.91	1.0	1.24	22.9
PAAWYYR6-5C25mm2-X	1.20	1.2	1.24	26.9
PAAWYYR6-5C35mm2-X	0.868	1.2	1.32	30.1
PAAWYYR6-5C50mm2-X	0.641	1.4	1.48	34.2
PAAWYYR6-5C70mm2-X	0.443	1.4	1.56	39.2
PAAWYYR6-5C95mm2-X	0.320	1.6	1.72	45.0

Technical data

Rated voltage	0.6/1 kV
Dielectric Strength	AC 3500V, 5min, no breakdown
Rated temperature	-15°C ~ 70°C
RoHS	Compliant
Min. bending radius	10D (D= overall diameter)
Flame retardant	IEC 60332-1-2

Marking on cable

PROSE _ PAAWYYR6-XCXXmm2-X _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within $\pm 0.5\%$ accuracy.
Remark2: PAAWYYR6-XCXXmm2-X means the product number, and the PN in the actual order shall prevail.
Remark3: (DD+MM+SS+YY+NNNNN) means cable code.
Remark4: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.