

- 19" standard rack configuration
- Removeable side pane
- Cable entry via roof and base
- Lockable front & rear door
- single & double open option
- Height available from 18U to 47U
- Width available with 600/800mm
- Depth available with 600/800/1000/1100/1200mm
- Static loading capacity 600~1200kg
- Levelling feet & castor



Part number						
PRNC1X-XXXXXXX		Service & Network cabinet				
1 23 4 567						
1. 1X Static loading capacity	2. X Width	3. X Depth	4. XX Height (U)	5. X Front door	6. X Rear door	7. X Color
1A: 600kg 1B: 800kg 1C: 1000kg 1D: 1200kg	6-600mm 8-800mm	6-600mm 8-800mm 0-1000mm 1-1100mm 2-1200mm	18 22 42 47	A-Single perforated B-Double perforated C-Solid steel D-Tempered glass E-Waist hole glass door F-Round hole glass door	A-Single perforated B-Double perforated	A-RAL9005 B-RAL7035

Reference structure

Exploded view diagram of the server cabinet showing various components labeled 1 through 13. The diagram illustrates the assembly of the cabinet, including the top panel, frame, side brace, vertical mounting rail, fixed shelf, A type door, F type door, E type door, D type door, B type door, C type door, side panel, and bottom panel.

1.Top panel

2. Frame

3. Side brace

4. Vertical mounting rail

5. Fixed shelf

6. A type door

7. F type door

8. E type door

9. D type door

10. B type door

11. C type door

12. Side panel

13. Bottom panel

(Picture for reference)

Available PN

PN	Capacity (U)	Width (mm)	Depth (mm)	Ref. Height (mm)
PRNC1X-6618XXX	18	600	600	988
PRNC1X-6818XXX			800	
PRNC1X-6622XXX	22	600	600	1166
PRNC1X-6822XXX			800	
PRNC1X-6627XXX	27	600	600	1388
PRNC1X-6827XXX			800	
PRNC1X-6632XXX	32	600	600	1610
PRNC1X-6832XXX			800	
PRNC1X-6637XXX	37	600	600	1833
PRNC1X-6837XXX			800	
PRNC1X-6037XXX			1000	
PRNC1X-6237XXX			1200	
PRNC1X-6642XXX	42	600	600	2055
PRNC1X-6842XXX			800	
PRNC1X-6042XXX			1000	
PRNC1X-6142XXX			1100	
PRNC1X-6242XXX			1200	
PRNC1X-8642XXX		800	600	
PRNC1X-8842XXX			800	
PRNC1X-8042XXX			1000	
PRNC1X-8142XXX			1100	
PRNC1X-8242XXX			1200	
PRNC1X-6647XXX	47	600	600	2280
PRNC1X-6847XXX			800	
PRNC1X-6047XXX			1000	
PRNC1X-6147XXX			1100	
PRNC1X-6247XXX			1200	
PRNC1X-8647XXX		800	600	
PRNC1X-8847XXX			800	
PRNC1X-8047XXX			1000	
PRNC1X-8147XXX			1100	
PRNC1X-8247XXX			1200	

Note: The above product is the default and can be customized according to customer.

Accessories

Part	Qty.	Unit	Remark
Heavy duty castor	4	pcs	2"
M12 adjustable feet	4	pcs	/
Fixed shelf	3	pcs	1 piece for 18~32U cabinet
M6 Cage nut and screw	40	set	20 sets for 18~32U cabinet

Material

Material	Cold rolled steel (SPCC)
Surface finished	Powder coating, colors available in black(RAL9005) or gray(RAL7035)

Environment

Working temperature	-40℃ to +70℃
IP Rating	IP20
RoHS	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.