


MW-V09S23

0.9m 23GHz High Performance Microwave Antenna



- High Performance Antenna
- 21.20-23.60 GHz
- Single-Polarized



Electrical Data

Operating Frequency		21.20-23.60 GHz
Gain*	Low	43.4 dBi
	Mid	44.2 dBi
	High	44.7 dBi
3dB BW (Azimuth & Elevation)		1.0 deg
Regulatory Compliance		ETSI 302 217 R3 Class3 US FCC Part 101A
RPE Number		RPE09-23
VSWR (Return Loss)		1.30 (-17.7 dB)
F/B Ratio		71 dB
XPD		30 dB
Polarization		Single-polarized
Interface Waveguide Type		WR42 (BJ220)

* Tolerance : ±1.0dBi.

Environmental Data

Operating Temperature		-55°C to +70°C
Storage Temperature		-55°C to +70°C
Wind resistance	Operational	180 km/h
	Survival	252 km/h

Mechanical Data


Reflector Construction		One-piece reflector
Adjustment	Azimuth	±15°
	Elevation	±15°
Packed Dimension	L / W / H	1065mm / 1065mm / 415mm
Packing		1 set in cardboard box
Net Weight		22Kg (48.5LB)
Gross Weight		33Kg (72.8LB)

MW-V09S23

0.9m 23GHz High Performance Microwave Antenna


PROSE

Antenna Dimension (in mm) and Mounting Kit



Pole diameter	90-120 mm
Side struts, included	0

Wind Forces at Wind Velocity Survival Rating



Axial Force (FA)	2949 N
Side Force (FS)	1455 N
Twisting Moment (MT)	1180 N.M
Angle α for MT Max	-10°

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.