

- Foamed PE Insulation Coaxial Cable
- Tape + Braiding Shield
- Black PE jacket
- Recommended operating frequency: 30~3000 MHz
- This product is used for telecommunication system




Photo for reference

Material

Inner conductor material	Copper Clad Aluminum, solid
Dielectric material	Foamed PE
Shield 1 material	Al foil
Shield 2 material	Tinned copper wire braiding
Jacket material	PE, Black

Dimensions

Inner conductor OD.	Ø 1.8 mm
Dielectric OD.	Ø 5.0 mm
Shield 1 OD.	Ø 5.2 mm
Shield 2 OD.	Ø 5.78 mm
Jacket OD.	Ø 7.5 mm

Electrical data

Impedance	50±2 Ω
Capacitance	82±2 pF/m
Relative Velocity of Propagation	81 %
Dielectric strength	1600V
Shielding effectiveness	>80dB
VSWR	≤1.20 @30-2700MHz
Max. Operating Voltage	2000V
Max. Operating Frequency	3GHz

Mechanical data

Min. bending radius	38 mm
---------------------	-------

Environmental data

Operating Temperature	-40°C to +80°C
RoHS	Compliant

Attenuation (@air temperature of +20°C)

Frequency (MHz)	Attenuation (dB/100m)
150	7.8
280	10.8
350	12.1
400	13.0
800	18.9
900	20.2
1200	23.7
1500	26.8
1800	29.7
1900	30.6
2000	31.5
2200	33.3
2500	35.8
3000	40.9

*Maximum attenuation value shall be 105% of the nominal attenuation value.

Marking on cable

PROSE _ 5D-FB PET4 _ _ _ _ (DD+MM+SS+YY+NNNNN) _ _ _ _ XXXXm
Remark1: Printing Interval: 1m, within $\pm 0.5\%$ accuracy.
Remark2: (DD+MM+SS+YY+NNNNN) means cable code.
Remark3: XXXXm means cable meter.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.