

Main Features

- Low PIM with cable termination design
- Wide frequency band
- Low VSWR
- Excellent capacity in anti-pulse and burnout
- Easy to be installed
- Customized connector is available

Electrical Specifications

Attenuation value & Accuracy(dB)										VSWR	Power handling
5	6	7	8	10	13	15	20	30	40		
±1.2	±1.2	±1.2	±1.2	±1.5	±1.5	±1.5	±1.5	±1.8	±1.8	1.25	50W(20°C)

*XX refer to attenuation in dB

Intermodulation(3rd) ≤-155dBc@2×20W


Environmental Specifications

Operating temperature range	-30°C to +70°C
Storage temperature range	-40°C to +85°C
Relative humidity	0%- 95%
Barometric pressure	55KPa -106KPa
Applications	Indoor

Mechanical Specifications

Dimension	158×220×108 (mm, excluding brackets and connectors)
Weight	≤3.5kg
Connectors type	4.3-10 male to 4.3-10 female
Mounting	Wall or pole
Packing	1Pcs in box

Outline Drawing



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.