

Main Features

- Low VSWR, low insertion loss
- Low PIM, high reliability
- High power handling
- High directivity between output and coupling port
- Compact design for easy installation
- Customized connector is available
- Optional values for coupling port
- Support 5G frequency band



Electrical Specifications

Items	Value	
Frequency	698 - 3800MHz	
Return loss	≤-19dB	
Attenuation values	Coupling attenuation	Distribution loss
5dB: DC-5-9F-64F-07-T	5±1.0dB	≤2.1dB
6dB: DC-6-9F-64F-07-T	6±1.0dB	≤1.7dB
7dB: DC-7-9F-64F-07-T	7±1.0dB	≤1.5dB
8dB: DC-8-9F-64F-07-T	8±1.0dB	≤1.4dB
10dB: DC-10-9F-64F-07-T	10±1.2dB	≤1.0dB
12dB: DC-12-9F-64F-07-T	12±1.2dB	≤0.6dB
13dB: DC-13-9F-64F-07-T	13±1.2dB	≤0.6dB
15dB: DC-15-9F-64F-07-T	15±1.2dB	≤0.5dB
20dB: DC-20-9F-64F-07-T	20±1.5dB	≤0.4dB
25dB: DC-25-9F-64F-07-T	25±1.5dB	≤0.4dB
30dB: DC-30-9F-64F-07-T	30±1.5dB	≤0.3dB
35dB: DC-35-9F-64F-07-T	35±1.8dB	≤0.3dB
40dB: DC-40-9F-64F-07-T	40±1.8dB	≤0.3dB
Directivity	20dB	
Power handling	500W	
Intermodulation (3rd order)	≤-160dBc@2x43dBm	
Impedance	50Ω	


Environmental Specifications

Items	Value
Operating temperature range	-30°C to +70°C
Storage temperature range	-40°C to +85°C
Relative humidity	0%- 95%
Barometric pressure	55KPa -106KPa
Applications	IP65

Mechanical Specifications

Items	Value
Dimension	128 x47 x 30 (mm)
Weight	500g
Connectors type	4.3-10 female
Mounting	Rack
Packing	1Pcs in box

Outline Drawing



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.