

Main Features

- Low VSWR, low insertion loss
- Low PIM, high reliability
- High power handling
- Compact design for easy installation
- Customized connector is available
- Optional values for coupling port

Electrical Specifications

Items	Value	
Frequency	380-4200MHz	
VSWR	≤1.4	
Attenuation values	Coupling attenuation	Distribution loss
5dB: T-5-0342-43F-163-01	5±1.5	≤2.5dB
6dB: T-6-0342-43F-163-01	6±1.5	≤1.9dB
7dB: T-7-0342-43F-163-01	7±1.5	≤1.3dB
10dB: T-10-0342-43F-163-01	10±2	≤1.0dB
15dB: T-15-0342-43F-163-01	15±2	≤0.8dB
20dB: T-20-0342-43F-163-01	20±2	≤0.6dB
30dB: T-30-0342-43F-163-01	30±2	≤0.5dB
Power handling	500W	
Intermodulation (3rd order)	≤-163dBc@2x43dBm	
Impedance	50Ω	


Environmental Specifications

Items	Value
Operating temperature range	-30°C to +70°C
Storage temperature range	-40°C to +85°C
Relative humidity	0%- 95%
Barometric pressure	55KPa -106KPa
Applications	IP65

Mechanical Specifications

Items	Value
Dimension	107 x 25 x 25 (mm)
Weight	0.65kg
Connectors type	4.3-10 female
Mounting	Plane
Packing	1Pcs in box

Outline Drawing



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.