

Main Features

- Low VSWR, low insertion loss
- Low PIM, high reliability
- High power handling
- Compact design for easy installation
- Customized connector is available
- Optional values for coupling port

Electrical Specifications

Items	Value	
Frequency	350-520/555-960/1710-2700/3500-4500/4900-6000MHz	
VSWR	≤1.5	
Attenuation values	Coupling attenuation	Distribution loss
5dB: T-5-0360-DF-160-01	5±1.8	≤1.5dB
6dB: T-6-0360-DF-160-01	6±1.8	≤1.3dB
7dB: T-7-0360-DF-160-01	7±1.8	≤1.2dB
8dB: T-8-0360-DF-160-01	8±1.5	≤1.0dB
10dB: T-10-0360-DF-160-01	10±1.5	≤0.8dB
15dB: T-15-0360-DF-160-01	15±2.0	≤0.6dB
20dB: T-20-0360-DF-160-01	20±2.0	≤0.4dB
30dB: T-30-0360-DF-160-01	30±3.5	≤0.4dB
Power handling	500W	
Intermodulation (3rd order)	≤-160dBc@2x43dBm	
Impedance	50Ω	


Environmental Specifications

Items	Value
Operating temperature range	-30°C to +70°C
Storage temperature range	-40°C to +85°C
Relative humidity	0%- 95%
Barometric pressure	55KPa -106KPa
Applications	IP65

Mechanical Specifications

Items	Value
Connectors type	7/16 DIN female
Mounting	Plane
Packing	1Pcs in box

Outline Drawing



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.