



Photo for reference


Part number




S-DC-CAC	Cold aisle containment, double-door
----------	-------------------------------------

Specification

Material	SPCC, tempered glass
Surface treatment	Powder coated
Color	Black (RAL9005)
Size	H2320*W3600*D (depends on rack quantity)
Time of impact	The system has an adjustable delay of 10 to 20 seconds after the alarm to allow occupants to exit the area when a fire is detected.
Accessory	
Rack name	02 pieces/cabinet
Rack row name	02 pieces/row

Product drawing







Part list

Item	Part	Description	Material & Finish	QTY	Unit
1	Front door	With door cabinet, W3600*H2320*D207mm	SPCC, Powder coated RAL9005	1	set
2	Rear door	With door cabinet, W3600*H2320*D207mm	SPCC, Powder coated RAL9005	1	set
3	Fixed steel skylight for functional part	For sensors, camera installation W1370*D600*H38.3mm	SPCC, Powder coated RAL9005	2	pcs
4	Polycarbonate plastic flipping skylight	Automatically opens when receiving fire signals W1370*D600*H42mm 1. Ceiling panel is held by the magnetic attraction, and stops being attracted to release the ceiling panel when there is a control signal. 2. The opening angle of the ceiling panel after flipping must be at least greater than 75 degrees. 3. Minimum 65% Area is calculated by the air space that can pass through.	Polycarbonate plastic	pending	pcs

		4. The ceiling panels will be activated to flip according to the signal of the fire protection system to ensure effective firefighting. 5. Ceiling panels do not collide when flipped.			
5	Fixed polycarbonate plastic skylight	W1370*D600*H42mm	Polycarbonate plastic	pending	pcs
6	Skylight bracket	W1370*D600mm	SPCC, Powder coated RAL9005	pending	pcs
7	Server racks	pending	SPCC, Powder coated RAL9005	pending	pcs
8	Sound and light alarm	There are warnings to alert the user about the release of the ceiling panel.	plastic	1	pcs

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.