

PR-DMB-12R01-HD-DRMB-V3-XM

1/2" coaxial jumper with weatherproof kit, low loss

PROSE




Photo for reference

Part number

PR-DMB-12R01-HD-DRMB-V3-xM	RF coaxial jumper with weatherproof kit, low loss
*xM indicate the length, unit meter	

Part list

Connector 1	DIN male straight
Connector 2	DIN male angled
Cable	1/2" coaxial cable, low loss, PE jacket, foam PE insulation
Bend protection	Molding or clamp
Weatherproof 1	Rubber boot for DIN male, straight
Weatherproof 2	Rubber boot for DIN male, angled
Label	Wrap sticker

Electrical data

Characteristics impedance	50Ω
Frequency	DC to 3GHz
Propagation velocity	≥87%
Connector insertion loss, typical	$\leq 0.05 \cdot \sqrt{F} \text{ GHz dB}$
Cable attenuation (by meter)	$\leq 0.064 @ 703\text{-}803\text{MHz}$
	$\leq 0.071 @ 890\text{-}960\text{MHz}$
	$\leq 0.1 @ 1710\text{-}1880\text{MHz}$
	$\leq 0.11 @ 1920\text{-}2170\text{MHz}$
	$\leq 0.124 @ 2170\text{-}2700\text{MHz}$
Assembly insertion loss	Cable attenuation+ connection loss ($0.1 \cdot \sqrt{F} \text{ GHz}$)
Return loss	≥28dB @703-803MHz
	≥28dB @890-960MHz
	≥28dB @1710-1880MHz
	≥28dB @1920-2170MHz

	≥26dB @2170-2700MHz
Intermodulation (3rd Order)	≤-155dBc @2x43 dBm

Mechanical data

Minimum bending radius	Single	≤70mm
	Repeated	≤130mm
Connector torque proof recommend	25 to 30 NM	

Environment

Working temperature	-50℃ to +85℃
Halogen free	IEC 60754-2:2011
UV resistance	UL 1581
IP protection	IP68, IEC 60529
2011/65/Eu (RoHS)	Compliant

Part list specification

Cable	
Inner conductor	Copper clad aluminum, smooth solid tube, 4.8mm
DC resistance	≤1.57Ω/km
Outer conductor	Corrugated copper, SIN wave, 13.8mm
DC resistance	≤2.7Ω/km
Jacket	Black PE, 15.9mm±2%
Weight	≥0.2kg/m
Maximum tensile strength	≥1050N
Connector	
Inner contact	Bronze/brass contact with silver plated
Insertion loss, typical	≤0.05*√F GHz dB
Outer conductor	Brass, Cu-Sn-Zn Tri-alloy plated
Weight	≥86g
Weatherproof silicone boot	
Technical data	
Material	Silicone, black
Suitable cable	13-17mm
Suitable connector	DIN male straight DIN male angled
Weight	≥54g
Photo for reference	
	

PR-DMB-12R01-HD-DRMB-V3-XM

1/2" coaxial jumper with weatherproof kit, low loss

PROSE

Temperature rating	-55°C to +90°C
Temperature storage	-55°C to +90°C
Weatherproof	IEC60529, IP68
UV resistance	IEC60068-2-5, 1000h
RoHS	Compliance

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.