


PR-CSTX-40A-XXX-BK

Cold shrink tube $\phi 40\text{mm}$

PROSE

- Reliable seal against water
- 2 layers on the connector side
- Tough, resilient rubber holds press seal even after exposure
- Eliminates need for heat source or special tools
- Easy installation and save times
- Resistant to fungus, ozone, alkalis and acids



Part number

PR-CSTX-40A-XXX-BK 1 2 3 4	Cold shrink tube $\phi 40\text{mm}$
*1, CSTX indicates the cold shrink tube type, 2layers on connector side *2, 40A indicates the inner core diameter *3 XXX indicates the rubber length after extracting *4 XX indicates the rubber color, BK-Black	

Material

Rubber	Silicone rubber
Plastic core	PE/PC

Dimensions

Inner diameter (plastic core)	40mm
Inner diameter after extracting (rubber tube)	$\leq 12\text{mm}$
Thickness after extracting (rubber tube)	3.0mm
Length after extracting (rubber tube)	As request

Technical data

Hardness, Shore A	40
Tensile strength	9.0MPa
Elongation at break	820%
Tear strength	32kN/m

Environment

Operating temperature	-40°C to +90°C
Flammability	UL94-V1
UV resistance	Pass
IP protection	IP68, IEC 60529
RoHS	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.