

PR-RC2-DM-L-C05

DIN male connector for 7/8" coaxial leaky cable

PROSE

- 50Ω impedance
- DIN male interface
- Field installation
- Frequency up to 3.8GHz
- Good return loss and intermodulation performance




Photo for reference

Part number

PR-RC2-DM-L-C05	DIN male connector for 7/8" coaxial leaky cable
-----------------	---

Electrical data

Characteristics impedance	50Ω
Frequency	DC to 3.8GHz
Insulation resistance	≥5GΩ
Center contact resistance	0.5mΩ
Outer contact resistance	0.25mΩ
Dielectric withstanding voltage	4000V rms
Operating voltage	500V rms
Insertion loss	≤0.12dB
VSWR	≤1.10 @ DC-1.0GHz
	≤1.15 @ 1.0-2.7GHz
	≤1.20 @ 2.7-3.8GHz
Intermodulation (3 rd Order)	≤-158dBc @1800MHz, 2x43dBm

Mechanical data

Interface	DIN male
Suitable cable	7/8" coaxial leaky cable
Mating cycles	≥500 times
Connector torque proof recommend	25 to 30N.m

Environment

Working temperature	-45°C to +85°C
Shock test method	MIL-STD-202, method 213, condition D
Vibration test method	MIL-STD-202, method 204, condition A
RoHS	Compliant

Notice

- 1, The connection should be covered with addition weatherproof kits for long time duration.
- 2, Connection molding shape may be changed during the product life-time due to the manufacture skill upgrade.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.