

- Suitable for duplex LC/SC adapters or duplex SC adaptor installation and usage
- Suit for cables below $\Phi 12$ terminal and figure 8 type and $\Phi 3$ drop cables protecting connection
- The box has turnover structure cover, compact size
- IP55
- Suitable for wall-mounting or pole-mounting installation
- Suitable for outdoor cable or indoor soft cable



Part number

PRFDB-DW1-XXXX-XXXXXX-X	Fiber optic distribution box
1 2 3 4 5 6	
*1 indicate capacity: 02=2 cores, 04=4 cores, 08=8 cores...	
*2 indicate adapter style: SC=SC/UPC, SCA=SC/APC, DLC=DLC/UPC, DLCA=DLC/APC...	
*3 indicate splitter: 00=no splitter, 01=1:2, 02=1:4, 03=1:8, 04=2:8...	
*4 indicate pigtail: 0=without 0.9mm pigtail, 1=with 0.9mm pigtail, 2=with 2.0mm pigtail, 3=with 3.0mm pigtail...	
*5 indicate pigtail fiber type: 0=without pigtail, SM1=G652D fiber, SM2=G657A1 fiber, SM3=G657A2 fiber...	
*6 indicate application: W=wall-mounting, P=pole-mounting...	

Specification

Dimension(mm)	L220*W175*H50 (for reference)
No. of inlet and outlet ports	1 in 2 out
The maximum capacity	12 fibers
Material	PC+ABS

Environmental data

Operation temperature	-25°C ~ +55°C
Storage temperature	-40°C ~ +70°C
2011/65/EC (RoHS)	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.