

PWYY5AT-ST-2C10mm2-4

Shielded power cable



- High grade copper wire
- TC/PVC/TBS/PVC
- Rated temperature: 70°C
- This product used for power transmission




Photo for reference

Part number

| Part No.             | Description                                                                                                                                                                         |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PWYY5AT-ST-2C10mm2-4 | Power cable, 0.6/1kV, 2x10mm^2, Stranded tinned copper wire conductor, Black and Grey PVC insulation, AL foil tape wrapping + Tinned copper wire braiding screen, Black PVC sheath, |

Colour code

|                                |
|--------------------------------|
| Insulation colour: Black, Grey |
| Sheath colour: Black           |

Material and dimension

| No. | Item       |                                           | PWYY5AT-ST-2C10mm2-4        |
|-----|------------|-------------------------------------------|-----------------------------|
| 1   | Conductor  | Material                                  | Stranded tinned copper wire |
|     |            | Quantity                                  | 2 cores                     |
|     |            | Nominal cross-section area                | 10mm^2                      |
|     |            | Approximate diameter of single metal wire | 0.51mm                      |
| 2   | Insulation | Material                                  | PVC                         |
| 3   | Filler     | Material                                  | PVC                         |
| 4   | Shield     | Inner Tape Material                       | AL foil wrapping            |
|     |            | Outer Braiding Material                   | Tinned copper wire braiding |
|     |            | Braiding Coverage                         | ≥60%                        |
| 5   | Sheath     | Material                                  | PVC                         |
|     |            | Overall diameter, approximate             | ≈15.8mm                     |
|     |            | Cable weight, approximate                 | ≈540kg/km                   |

Technical data

|                     |                              |
|---------------------|------------------------------|
| Rated voltage       | 0.6/1kV                      |
| Dielectric strength | AC 3500V, 5min, No breakdown |

|                                 |               |
|---------------------------------|---------------|
| Max. Conductor resistance, 20°C | ≤2.04Ω/km     |
| Insulation resistance at 20°C   | ≥7MΩ·km       |
| Operating temperature           | -50°C ~ +70°C |
| Installation temperature        | -10°C ~ +50°C |
| Storage temperature             | -50°C ~ +70°C |
| RoHS                            | Compliant     |
| Flame retardant                 | IEC 60332-1-2 |

## Packing

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| Cable drum size, approximate | 1000*1000*720 mm                                                                   |
| Minimum packing length       | 500m/drum                                                                          |
| Other requirement            | Except for the tail drum, the length per drum shall be in multiples of 100 meters. |

## Marking on cable

|                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------|
| PROSE _ PWYY5AT-ST-2C10mm2-4 _ _ _ 2x10mm <sup>2</sup> _ _ _ 0.6/1kV _ _ _ _ (DD+MM+SS+YY+NNNNN)_ _ _ _ _ XXXXm |
| Remark1: Printing Interval: 1m, within ±0.5% accuracy.                                                          |
| Remark2: (DD+MM+SS+YY+NNNNN) means cable code.                                                                  |
| Remark3: XXXXm means cable meter.                                                                               |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.