

Main Features

- Support 2x2 MIMO for band 1/3, and 4x4 MIMO for n78
- Support 3G, 4G, 5G technologies
- Suitable for large-scale indoor installations / Neutral Host / Multi-Operator applications
- Hybrid DC/Fiber Feed for plug and play installation
- Features remote-control and monitoring



Electrical Specifications

		Uplink	Downlink
Frequency	Band 1 (2x2 MIMO)	1920 - 1980 MHz	2110 - 2170 MHz
	Band 3 (2x2 MIMO)	1710 - 1785 MHz	1805 - 1880 MHz
	n78 (4x4 MIMO)	3410 - 3800 MHz	3410 - 3800 MHz
Gain	Band 1/3	31 ± 2 dB	31 ± 2 dB
	n78	31 ± 2 dB	31 ± 2 dB
RF output power	Band 1/3	---	21 ± 1 dBm (RF per band per port)
	n78	---	24 ± 1 dBm (RF per port)
Antenna gain		3 dBi @ 1.7-2.7GHz	3 dBi @ 1.7-2.7GHz
		5 dBi @ 3.3-3.8GHz	5 dBi @ 3.3-3.8GHz

Environmental Specifications

Operating temperature range	-10 °C to +45 °C
Storage temperature range	-40°C to +85°C
Relative humidity	10% - 95%
Ingress protection	IP50
Monitoring and control	Remote control via IM2U/PBMU

Mechanical Specifications

Optical connector	4 x SC/APC (4x4 MIMO port)
Installation	Celling, wall or pole mounted
Antenna	Omni antenna Integrated

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.