

PR-FPP01-XXX-XX

Flexible pipe PVC with different size

PROSE

- Air-and liquid-tight
- Good resistant to oil, acid, and solvents
- Racking resistant, good mechanical strength
- HB according to UL94



Part number

PR-FPP01-XXX-XX	Flexible pipe PVC with different size
1 2 3	
*1 FPP01 indicate conduit type	
*2 XXX indicates the pipe dimension	
*3 XX indicates the pipe color, BK=Black, WH=White, GY=Gray	
E.g. PR-FPP01-100-BK, means flexible pipe dimension 10mm, black	

Available PNs

Part Number	Size (mm)	Ref. Outer diameter (mm)	Ref. bending radius (mm)	Standard length/roll (m)
PR-FPP01-080-XX	5.7x8.0	8.0	35	100
PR-FPP01-100-XX	6.5x10.0	10.0	35	100
PR-FPP01-130-XX	9.5x13.0	13.0	45	100
PR-FPP01-158-XX	12.0x15.8	15.8	55	100
PR-FPP01-185-XX	14.3x18.5	18.5	65	100
PR-FPP01-212-XX	17.0x21.2	21.2	75	50
PR-FPP01-255-XX	21.0x25.5	25.5	85	50
PR-FPP01-285-XX	23.0x28.5	28.5	100	50
PR-FPP01-345-XX	29.0x34.5	34.5	120	25
PR-FPP01-425-XX	36.0x42.5	42.5	150	25
PR-FPP01-545-XX	48.0x54.5	54.5	190	25
PR-FPP01-672-XX	56.0x67.2	67.2	270	10
PR-FPP01-800-XX	66.5x80.0	80.0	350	10
PR-FPP01-1060-XX	91.0x106.0	106.0	450	10

*XX indicate the color

Accessories

PR-FPP01-SC-XX	PVC Flexible pipe straight connector	
----------------	--------------------------------------	--

Material

Body material	PVC
---------------	-----

Environment

Working temperature	-15°C to +70°C
Fire resistance	UL94-HB
RoHS	Compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.